Basic Peristaltic Pump

WT600-2J



Flow Rates

20000 mL/min

4.2-12000 mL/min

Pump Head Option



YZ1515x
YZ2515x



YZII15
YZII25



KZ25




DG15-24

Speed	60rpm-600rpm, CW/CCW
Speed resolution	1rpm
Speed accuracy	≤±1%
Control mode	Control panel, external signal control and communication control are available
Display	3-digit LED display for current speed
External control	Start/stop, direction and speed control (4-20mA, 0.5-5V, 1-10V, 1-10kHz external control module optional)
Communication interface	RS485
Power-off memory	Return to previous state when power on
Prime	For fast filling and emptying at full speed
Dimension (L×W×H)	285×207×180 (mm)
Power supply	AC 220V±20%/200W or AC 110V±20%/200W
Operating temperature	0 to 40℃
Relative humidity	＜80%
IP rating	IP31
Weight	5.2kg

Mainly used in laboratorial application. With brushless motor, can drive multi-pump heads.

CE LAB INDUSTRIAL





Model (Product code, Power supply)	Pump Head	Tubing	Flow Rate (mL/min)	Weight (kg)
WT600-2J-A (05.02.63A, AC220V)	(1,2, 3,4)×YZ1515x	13# 14# 19# 16# 25# 17# 18#	4-2200 (Single Channel)	5.6-6.8
	(1,2,3,4)×YZII15			
	(1,2,3,4)×YZ2515x	15# 24#	100-1600 (Single Channel)	
WT600-2J-B (05.02.63B, AC110V)	(1,2)×YZII25	15# 24# 35# 36#	100-3000 (Single Channel)	5.6-6.0
	DG15-24	16# 25# 17#	50-1800 (Single Channel)	6.0
	(1,2)×KZ25	15# 24# 35# 36#	200-6000 (Single Channel)	6.0-6.8